

INTERTEK DIRECTORY OF BUILDING PRODUCTS

Al Talah – FD90 SD – 64mm thick Palm Strand Board Fire Door Core - 90-Minute - UL 10C/UL 10B/ NFPA 252

Company: Al Talah Board Manufacturing Company Ltd

Product Covered

Al Talah – FD90 SD – 64mm thick Palm Strand Board Fire Door Core - 90-Minute – UL 10C/UL 10B/ NFPA 252

Product Description

Door leaf core is constructed using Palm Strand Board and Calcium Silicate Board layers with overall leaf thickness: 64mm.

Tested Door Size: 1000 x 2300 x 64mm (w x h x thickness)

FIRE RATINGS

The product noted above has been evaluated according to the requirements of the standard UL 10C and has qualified for up to **90 minutes (1 ½ hour)** positive pressure fire rating.

Also meets the requirements of UL 10B (Neutral Pressure Fire Rating) and NFPA 252 (Positive Pressure Fire Rating).

[LISTING REPORT](#) [CERTIFICATE OF COMPLIANCE](#) [RETURN TO SEARCH](#)

ATTRIBUTES

Certificate Date of Expiry	December 31, 2025
Certificate Date of Initial Registration	July 11, 2024
Certificate Number	WHI24-39132911
Criteria	UL 10(c) (2016)
Criteria	UL 10(b) (2008) (R2020)
Criteria	NFPA 252 (2022)
CSI Code	08 10 00 Doors and Frames
Fire Resistance	1-1/2 Hour Fire Rating
Listing Section	FIRE DOOR COMPONENTS
Spec ID	78371

DESIGN DOCUMENTS

No Results

PUBLIC DOCUMENTS

No Results



Intertek [Warnock Hersey Mark](#)



Intertek [ETL Listed Mark](#)



© Intertek Group plc

All other product or service names are the property of their respective owners.

[Disclaimer](#)

[Terms](#)

[Privacy](#)

[Cookies](#)

[Client Portals](#)

TOTAL QUALITY.